



GuardALL[®]
Guard for ALL

PRODUCT
CATALOG

GuardALL

DRY POWDER

Dry Powder is highly versatile. Class A, B & C fire fighting medium suitable for most risk. In addition to dealing with electrical hazards, flammable liquids and gases, powder also effective for vehicle fires.



FIRE EXTINGUISHER



Wood, Paper,
Textile, Fabric



Petrol, Diesel,
Oils



Electrical



Magnesium, Titanium,
Potassium

TYPE	GAP-1	GAP-2	GAP-3	GAP-5	GAP-6	GAP-9
Height (cm)	31	42	46	51	51	63
Width (cm)	11	19	19	22	22	25
Diameter (cm)	8.9	11.1	12.7	14.6	14.6	17
Capacity (kg)	1	2	3	5	5	9
Weight full (kg)	1.6 ^o	3.3	4.4	6.7	6.7	13
Weight empty (kg)	0.6	1.3	1.4	1.7	1.7	4
Discharge time (sec)	8	13	14	15	15	21
Discharge range (m)	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12	3 to 12
Test pressure (bar)	25	25	25	25	25	25
Working pressure at 20°C	15	15	15	15	15	15
Minimum effective discharge (%)	90	90	90	90	90	90
Temperature range (0°C)	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60	-20 to 60
Fire rating	8A : 34B	21A : 70B	21A : 89B	29A : 165B	29A : 165B	43A : 233B

FOAM

Spray foam extinguishers are suitable for both A & B fire. Spray Foam has the ability to reduce the risk of reignition once the fire has been extinguished the foam effectively seals the vapours at the same time as cooling the fire.



Wood, Paper,
Textile, Fabric



Petrol, Diesel,
Oils

TYPE	GFO-6	GFO-9
Height (cm)	55	63
Width (cm)	25	25
Diameter (cm)	16.5	17
Capacity (kg)	6	9
Weight full (kg)	9.6	13.6
Weight empty (kg)	3	4
Discharge time (sec)	27	29
Discharge range (m)	3 to 12	3 to 12
Test pressure (bar)	25	25
Working pressure at 20°C	15	15
Minimum effective discharge (%)	90	90
Temperature range (0°C)	0 to 60	0 to 60
Fire rating	13A : 144B	21A : 183B

CO₂

CO₂ is suitable for electrical equipment, Class B fires and recognized for its non-damaging highly effective performance and cleanliness. GuardALL CO₂ have non-conductive anti-static horns. A protection to withstand extreme temperatures, dirty environment and UV degradation.



Petrol, Diesel,
Oil



Electrical

TYPE	GCO-2,2	GCO-3	GCO-5	GCO-6,8
Height (cm)	49	66	69	84
Width (cm)	18	18	25	33
Diameter (cm)	11	11	15	15
Capacity (kg)	2,2	3	5	6,8
Weight full (kg)	7.9	10,6	15,4	25,3
Weight empty (kg)	5,7	7,6	10,4	18,5
Discharge time (sec)	8	10	18	23
Discharge range (m)	3 to 12	3 to 12	3 to 12	3 to 12
Test pressure (bar)	200	200	200	200
Working pressure at 20°C	56	56	56	56
Minimum effective discharge (%)	90	90	90	90
Temperature range (0°C)	-20 to 60	-20 to 60	-20 to 60	-20 to 60
Fire rating	34B	36B	34B	77B

GuardALL



TROLLEY FIRE EXTINGUISHER

DRY POWDER TROLLEY

Trolley dry chemical powder fire extinguishers is best used where a large amount of fire extinguishing agent is required. The GuardALL trolley dry chemical powder can be used on Class A, B, C and E fires. Features include stainless steel cylinder, ultra-high UV powder coated red finish and a galvanised powder coated red trolley. Available in 25kg, 50kg, 68kg and 80kg sizes.

Type	25kg	50kg	68kg	80kg
Fire Class	Class A, B, C, E	Class A, B, C, E	Class A, B, C, E	Class A, B, C, E
Media	Dry Powder	Dry Powder	Dry Powder	Dry Powder
Range	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C	-20°C TO +60°C
Pressure	13.71 BAR (+20°C)	13.71 BAR (+20°C)	13.71 BAR (+20°C)	13.71 BAR (+20°C)



Wood, Paper,
Textile, Fabric



Petrol, Diesel,
Oils



Electrical



Magnesium, Titanium,
Potassium

AFFF FOAM TROLLEY

GuardALL's 25 Litre and 50 Litre AFFF Foam Mobile Extinguishers are best suited to Class A and B fires. These fires include ordinary combustibles such as wood, paper, plastics, rubber and rubbish as well as flammable and combustible liquids such as petrol. They have a stainless steel cylinder, ultra-high UV powder coated red finish and a galvanised red coated trolley.



Wood, Paper,
Textile, Fabric



Petrol, Diesel,
Oils

Type	25kg	50kg
Fire Class	Class A, B	Class A, B
Media	AFFF Foam	AFFF Foam
Range	-20°C TO +60°C	-20°C TO +60°C
Pressure	13.71 BAR (+20°C)	13.71 BAR (+20°C)

CO2 TROLLEY

Co2 is suitable for electrical equipment, Class B fires and recognized for its non-damaging highly effective performance and cleanliness. GuardALL Co2 have non-conductive anti-static horns. A protection to withstand extreme temperatures, dirty environment and UV degradation.



Petrol, Diesel,
Oil



Electrical

Type	25kg
Fire Class	Class B, C
Media	Co2
Range	-20°C TO +60°C
Test Pressure	25BAR

